



# 2747 siatur

optimised for sanding of fittings



## 2747 siatur



### Product profile

Grit type:	Silicon carbide
Grit range:	60-320; 400; 600-800
Backing:	jj-wt cloth, cotton
Coating:	Closed
bonding:	Resin over resin
Special coating:	Cooling additive

### optimised for sanding of fittings

As a specialist product for sanding fittings, the flexible silicon carbide belt 2747 siatur offers high adaptability to contours, curves and profiles and produces first-class results in applications ranging from deburring to structuring and final sanding of hard to grind metals and non-ferrous metals.

### Advantages

- This series is ideal for grinding fittings
- Excellent surface quality
- Highly adaptable to contours, curves and profiles

### Applications

- Surface treatment
- Deburring
- Blending
- Structuring and final sanding

### Abrasive formats

Cloth rolls; jumbolino; Various strips; Wide belts (width: from 400 mm); Hand sanding belts and sleeves (width: 30-390 mm/length: up to 950 mm); Narrow, edge and long belts (width: 25-399 mm/length: up to 8500 mm); Tongued sanding belts (width: 6-30 mm/length: up to 950 mm); strips assembly slashed

### Materials

Non-ferrous metal; Other hard-to-grind metals

### Use



Contact belt sanding



Stroke belt sanding



Slack-of-belt sanding



Power file



**Your Key to a Perfect Surface**  
**Your Key to a Perfect Surface**