



2820 siamet

the all-round sanding belt for unalloyed steel and non-ferrous metals



2820 siamet



Product profile

| | |
|------------------|------------------|
| Grit type: | Zirconia alumina |
| Grit range: | 36-320; 400 |
| Backing: | y-wt cloth |
| Coating: | Closed |
| bonding: | Resin over resin |
| Special coating: | Cooling additive |

the all-round sanding belt for unalloyed steel and non-ferrous metals

As a specialist product designed for dry sanding with high removal rates as well as excellent edge stability and tear resistance, 2820 siamet is suitable for a wide variety of jobs ranging from removal of rust or paint to welding preparation – whether on unalloyed steels or non-ferrous metals.

Advantages

- High edge stability, high tear resistance
- High performance for all metals
- Aggressive cut

Applications

- Removing paint
- Removing rust
- Weld preparation
- Removing discolouration
- Sanding down
- Surface treatment
- Deburring
- Blending

Abrasive formats

Cloth rolls; jumbolino; Various strips; siafix discs; Self-adhesive discs; Various discs; Wide belts (width: from 400 mm); Hand sanding belts and sleeves (width: 30-390 mm/length: up to 950 mm); Narrow, edge and long belts (width: 25-399 mm/length: up to 8500 mm); Tongued sanding belts (width: 6-30 mm/length: up to 950 mm); Spiral belts

Materials

Unalloyed / low-alloy steel; Non-ferrous metal

Use



Contact belt sanding



Contact wide belt sanding



Power file



Stroke belt sanding



mini angle grinder



Centreless belt sanding



Your Key to a Perfect Surface
Your Key to a Perfect Surface