

Technical data sheet

6260 ultradisc scm



MKP person responsible:	Deepak Mahajan
Status:	Ok
Approval:	28.10.2016

Classification	Public series
Product type:	Non woven abrasives
Main application area:	Metal


Product profile	
Grit type:	Aluminium oxide
Grit range (total):	
Backing:	Nonwoven
Coating:	Mechanical
bonding:	Resin over resin
Special coating:	
Equipment:	



Properties		Technology
Cut:	4 - little	- Offene Streuung
Lifetime:	4 - low	
Finishing:	10 - very good	
Flexibility:	6 - medium	
Contact pressure:	7 - strong	

Advantages	
Coatings & composites:	
Wood:	
Metal:	<ul style="list-style-type: none"> - Universal, wide range of applications - Highly flexible - Soft construction and flexible bonding ensure finest-quality surfaces - Good finish properties - May be used wet or dry
Panels:	

Applications	
Coatings & composites:	
Wood:	
Metal:	<ul style="list-style-type: none"> - Light deburring - Sanding of paints and old lacquer - Finishing to prepare for coating and electroplating - Fine sanding - Satin finishing - Removing discolouration
Panels:	

Material	Superordinate group	Subgroup
Coatings & composites:		
Wood:		
Metal:	High alloy steels High alloy steels Non-alloy / low-alloy steels Non-ferrous metals Non-ferrous metals	<ul style="list-style-type: none"> ● Stainless steel (inox) ● High-alloy steel ● Ferrous metal ● Non-ferrous metal ● Aluminium
Panels:		

Conversion forms	Upper conversion	Lower conversion
	Discs	- scm discs

Use	Superordinate group	Subgroup
	Portable machine sanding	<ul style="list-style-type: none"> ● Angle grinder
	Portable machine sanding	<ul style="list-style-type: none"> ● Mini angle grinder
Cut:	Dry applicationWet sanding	

Details	
No suitability for:	
Sanding recommendation:	
Safety recommendation:	<ul style="list-style-type: none"> - Follow the general EN safety recommendations - Follow the general FEPA safety recommendations - Use eye and face protection - Glove

Communication	
Claim:	perfect performance for a perfect surface finish
Copy:	Thanks to consistently high stock removal rates, 6260 ultradisc scm delivers the best possible results in the least amount of time. It is suitable for wet and dry applications and produces finest-quality surfaces thanks to its soft construction and flexible bonding.
Industrial Verticals:	



Communication				
Image material:	Product Top View (PTV)	Front side:	ID 4896	
		Reverse side:	ID 4896	
	Application image	Coatings & composites:	ID 563	
		Wood:		
		Metal:		
		Product show:		
		Macro shot:		
	Packaging image:			
	Product group image:			

- Main application
- Secondary application