



7983 siasponge flex

adapts perfectly to the workpiece



7983 siasponge flex



Product profile

Grit type:	Aluminium oxide
Grit range:	60; 100; 180-220
Backing:	PU foam (soft)
Coating:	Mechanical
bonding:	Elastic binder
Coating:	2-page

adapts perfectly to the workpiece

Be it curves, shapes or contours – an even and perfect sanding pattern can be achieved with 7983 siasponge flex. The extra-soft foam of siasponge flex ensures maximum conformability.

Advantages

- Colour coded for easy identification
- No risk of sanding through thanks to pressure-equalising foam
- Highly adaptable to contours, curves and profiles
- Low clogging
- Can be used many times
- Consistent performance throughout the life of the product
- May be used wet or dry

Abrasive formats

Pads; Discs

Use



Manual sanding for edges



Random orbit sander;
Rotary sander

Applications

- Keying of wood, metal and plastic prior to application of paint
- Fine sanding of primer filler
- Sanding of profiled and rounded workpieces
- Keying surfaces without altering the shape

Materials

Old paint; Old lacquer; Colour; Primer filler; Melamine sheet; NC lacquer; PU lacquer; Bodyfiller; Polyester lacquer; UV lacquer; Water-based varnish; Plastics; Solid surface material; Hardwood; Softwood; Plaster



Your Key to a Perfect Surface
Your Key to a Perfect Surface